

Product data sheet

Specifications



Surface Switch - 63A 415V - 3 switched pole - IP66 (grey)

S56SW363GY

Main

Range	WPS
Device short name	56 series
Product or component type	Rotary switch
Colour tint	Light grey
Motor M-rating AS3133	M300

Complementary

Control type	Rotary
Material	PC (polycarbonate)
Surface finish	Gloss
Installation direction	Vertical
Width	101 mm
Height	107 mm
Depth	108 mm
Rated current	63 AX
[Ue] rated operational voltage	415 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	1 gang
Number of poles	3
Mounting mode	Surface mounted
Cable cross section	16...25 mm²

Environment

IP degree of protection	IP66
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	500 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	11.2 cm
Package 1 width	10.5 cm
Package 1 Length	10.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile